

Woven Bull Line™ Polyester Pull Tape

Woven Bull-Line® POLYESTER Fiber

- Economical • Best burn-through (conduit cutting) resistance • Good blowability into conduit
- Accurate sequential foot or meter markings • Can also be factory pre-installed into conduit
- Available on reels in a wide variety of continuous lengths

WP25 LUBED #0901 BULL-LINE

0044 FT



A-D Technologies manufactures a wide range of high performance Bull-Line™ Pull Tape products to expedite cable installation. Choose from woven polyester tapes or aramid fiber tape products which are available in a variety of strengths and lengths. A single pull tape eliminates the additional labor required for string, rope or winch line combinations. All Bull-Line™ tape is manufactured with the Stiff-Tape™ lubrication coating, resulting in the high-est performance pull tape available in the industry. Whatever the choice, Bull-Line™ Pull Tapes have continually provided a superior alternative to plastic pull ropes in cable installations through all types of conduit. A-D Technologies Bull-Line™ Pull Tapes meet or exceed all pull line requirements of Bellcore GR-356-CORE "Generic Requirements for Optical Cable Innerduct and Accessories."

Related Documents:

Request A Quote

Part Number	Minimum Tensile Strength (Pounds / Kilograms)	Approximate Width	Reel Size	Full Pallet Size	Reels Per Pallet	Weight Per Reel** (lbs.)	Order
WP05 1000	500 / 227	1/4" (6 mm)	8"	42" Sq. x 47"	64	6	
WP05 3000	500 / 227	1/4" (6 mm)	11-3/4"	42" Sq. x 47"	36	15	
WP05 5000	500 / 227	1/4" (6 mm)	11-3/4"	42" Sq. x 47"	36	22	
WP05 10000	500 / 227	1/4" (6 mm)	11-3/4"	42" Sq. x 47"	27	42	
WP05 10000	500 / 227	1/4" (6 mm)	11-3/4"	48" Sq. x 47"	48	42	
WP10 1000	1000 / 455	7/16" (11 mm)	8"	42" Sq. x 47"	64	8	
WP10 3000	1000 / 455	7/16" (11 mm)	11-3/4"	42" Sq. x 47"	45	19	
WP10 5000	1000 / 455	7/16" (11 mm)	14-1/2"	42" Sq. x 47"	10	30	
WP10 5000	1000 / 455	7/16" (11 mm)	14-1/2"	48" Sq. x 47"	36	30	
WP10 10000	1000 / 455	7/16" (11 mm)	16"	48" Sq. x 43-1/2"	18	60	
WP12 1000	1250 / 568	1/2" (13 mm)	8"	42" Sq. x 47"	64	8	
WP12 3000	1250 / 568	1/2" (13 mm)	11-3/4"	42" Sq. x 47"	45	21	Add To Cart
BLWP12 3000	1250 / 568	1/2" (13 mm)	11-3/4"	48" Sq. x 64"	80	21	
WP12 5000	1250 / 568	1/2" (13 mm)	14-1/2"	42" Sq. x 43-1/2"	10	34	
BLWP12 5000	1250 / 568	1/2" (13 mm)	14-1/2"	48" Sq. x 27"	36	34	
WP12 10000	1250 / 568	1/2" (13 mm)	16"	48" Sq. x 43-1/2"	18	67	

WP15 1000	1500 / 682	9/16" (14 mm)	11-3/4"	42" Sq. x 47"	36	12	
WP15 3000	1500 / 682	9/16" (14 mm)	13 1/2"	42" Sq. x 47"	45	31	
WP15 5000	1500 / 682	9/16" (14 mm)	14-1/2"	42" Sq. x 43-1/2"	10	55	
WP15 5000	1500 / 682	9/16" (14 mm)	18"	48" Sq. x 43-1/2"	36	108	
WP15 10000	1500 / 682	9/16" (14 mm)	18"	42" Sq. x 43-1/2"	8	108	
WP18 1000	1800 / 818	5/8" (16 mm)	11-3/4"	42" Sq. x 47"	45	14	
WP18 3000	1800 / 818	5/8" (16 mm)	13-1/2"	42" Sq. x 47"	45	35	Add To Cart
WP18 5000	1800 / 818	5/8" (16 mm)	16"	42" Sq. x 43-1/2"	10	62	
WP18 5000	1800 / 818	5/8" (16 mm)	18"	48" Sq. x 43-1/2"	18	80	
WP18 10000	1800 / 818	5/8" (16 mm)	18"	42" Sq. x 43-1/2"	8	115	
WP18 900M	1800 / 818	5/8" (16 mm)	14"	42" Sq. x 47"	16	36	
WP18 2000M	1800 / 818	5/8" (16 mm)	18"	42" Sq. x 43-1/2"	8	80	
WP25 1000	2500 / 1136	7/8" (22 mm)	11-3/4"	42" Sq. x 47"	45	15	
WP25 1500	2500 / 1136	7/8" (22 mm)	11-3/4"	42" Sq. x 47"	45	24	
WP25 1500	2500 / 1136	7/8" (22 mm)	11-3/4"	48" Sq. x 47"	80	24	
WP25 3000	2500 / 1136	7/8" (22 mm)	14-1/2"	48" Sq. x 43-1/2"	36	50	Add To Cart
WP25 5000	2500 / 1136	7/8" (22 mm)	16"	42" Sq. x 43-1/2"	10	84	
WP25 5000	2500 / 1136	7/8" (22 mm)	18"	48" Sq. x 43-1/2"	18	109	
WP25 10000	2500 / 1136	7/8" (22 mm)	24"	42" Sq. x 43-1/2"	2	166	
WP25 10000	2500 / 1136	7/8" (22 mm)	24"	48" Sq. x 43-1/2"	4	166	
WP25 2000M	2500 / 1136	7/8" (22 mm)	18"	42" Sq. x 43-1/2"	8	109	
WP40 1000	4000 / 1818	5/8" (16 mm)	11-3/4"	42" Sq. x 47"	36	26	
WP40 1000	4000 / 1818	5/8" (16 mm)	11-3/4"	48" Sq. x 47"	64	26	
WP40 3000	4000 / 1818	5/8" (16 mm)	16"	42" Sq. x 43-1/2"	8	83	
WP40 5000	4000 / 1818	5/8" (16 mm)	24"	42" Sq. x 43-1/2"	2	137	
WP40 5000	4000 / 1818	5/8" (16 mm)	24"	48" Sq. x 43-1/2"	8	259	
WP60 1000	6000 / 2727	3/4" (19 mm)	14-1/2"	48" Sq. x 43-1/2"	36	37	
WP60 3000	6000 / 2727	3/4" (19 mm)	18"	42" Sq. x 43-1/2"	8	155	
WP60 3000	6000 / 2727	3/4" (19 mm)	24"	48" Sq. x 43-1/2"	18	155	
WP60 5000	6000 / 2727	3/4" (19 mm)	24"	42" Sq. x 43-1/2"	2	155	
WP60	6000 / 2727	3/4" (19 mm)	24"	48" Sq. x 43-	8	155	

5000

1/2"

A-D Technologies | Suite 300, 11400 Parkside Drive, Knoxville, TN, 37934 | 1-800-847-7661 | Fax: 1-865-223-5085
moreinfo@adtechnologies.com | [Privacy Policy](#)

